

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **KEMPERDUR Finish silk**
- **UFI:** HRW7-R066-9004-00W4
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 - Identified use: intended for professional use only!
- **Application of the substance / the mixture** Sealing
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** KEMPER SYSTEM GmbH & Co. KG
Holländische Strasse 32-36
34246 Vellmar
Deutschland / Germany
Telefon: +49 (0)561 / 8295-0
Telefax: +49 (0)561 / 8295-5110
E-Mail: MSDS@KEMPER-SYSTEM.COM
- **Further information obtainable from:** research & development
- **1.4 Emergency telephone number:** Medical Emergency information in case of poisoning:
Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240
(advisory service in German or English language)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226	Flammable liquid and vapour.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02 GHS07 GHS09

- Signal word

Warning

- Hazard-determining components of labelling:

Isophorondiisocyanate homopolymer
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
Solvent naphtha (petroleum), light arom.
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
dibutyltin dilaurate
2-ethylhexanal

- Hazard statements

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.
As from 24 August 2023 adequate training is required before industrial or professional use.

- 2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT:

Not applicable.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

Trade name: **KEMPERDUR Finish silk**

- vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- Description: Mixture: consisting of the following components.

- Dangerous components:

CAS: 53880-05-0 EC number: 931-312-3	Isophorondiisocyanate homopolymer Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	25-50%
CAS: 128601-23-0 EC number: 918-668-5	Aromatic hydrocarbons, C9 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	≥12.5-<20%
CAS: 140921-24-0 ELINCS: 411-700-4	1,6-hexanediy-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate Skin Sens. 1, H317	2.5-10%
CAS: 4098-71-9 EINECS: 223-861-6	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.25-<0.5%
CAS: 1065336-91-5 EC number: 915-687-0	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.25-<0.5%
CAS: 77-58-7 EINECS: 201-039-8	dibutyltin dilaurate Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; Skin Corr. 1C, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<0.25%
CAS: 123-05-7 EINECS: 204-596-5	2-ethylhexanal Flam. Liq. 3, H226; Repr. 2, H361; Skin Sens. 1B, H317	≥0.1-<0.5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information:

Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Do not leave affected persons unattended.
Personal protection for the First Aider.

- After inhalation:

Take affected persons out of danger area and lay down.
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

- After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment in case of complaints.

- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Protect unharmed eye.

- After swallowing:

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.

- For safety reasons unsuitable extinguishing agents:

Water with full jet

- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.
Nitrogen oxides (NO_x)
Carbon monoxide (CO)

- 5.3 Advice for firefighters

- Protective equipment:

Do not inhale explosion gases or combustion gases.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

Trade name: **KEMPERDUR Finish silk**

- **Additional information** (Contd. of page 2)
 Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Keep away from ignition sources.
 Avoid contact with skin and eyes

- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
 Prevent from spreading (e.g. by damming-in or oil barriers).
 Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Do not flush with water or aqueous cleansing agents

- **6.4 Reference to other sections** See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed receptacles.
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.

- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.

- **Information about storage in one common storage facility:** Store away from foodstuffs.

- **Further information about storage conditions:** Store in dry conditions.
 Protect from frost.
 Keep container tightly sealed.
 Recommended storage temperature: 5-30 °C

- **Storage class:** 3

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- Ingredients with limit values that require monitoring at the workplace:	
4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	
OEL	Long-term value: 0.005 ppm Sens
77-58-7 dibutyltin dilaurate	
OEL	Short-term value: 0.2 mg/m ³ Long-term value: 0.1 mg/m ³ as Sn

- **Regulatory information** OEL: 2021 CoP for the Safety, Health and Welfare at Work

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see item 7.

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures:** The usual precautionary measures are to be adhered to when handling chemicals.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

Trade name: **KEMPERDUR Finish silk**

(Contd. of page 3)

<p>- Respiratory protection:</p>	<p>When used properly and under normal conditions, breathing protection is not required. Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Respiratory protection - Gas filters and combination filters according to (DIN EN 141)</p>
<p>- Hand protection</p>	<div style="display: flex; align-items: center;">  <p>Protective gloves</p> </div> <p>Check protective gloves prior to each use for their proper condition. Only use chemical-protective gloves with CE-labelling of category III. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation After use of gloves apply skin-cleaning agents and skin cosmetics.</p>
<p>- Material of gloves</p>	<p>Recommended materials: Butyl rubber, BR Recommended thickness of the material: ≥ 0.5 mm Penetration time (min.): < 480 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.</p>
<p>- Penetration time of glove material</p>	<p>The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.</p>
<p>- As protection from splashes gloves made of the following materials are suitable:</p>	<p>Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.1 mm Penetration time (min.): < 10</p>
<p>- Eye/face protection</p>	<div style="display: flex; align-items: center;">  <p>Tightly sealed goggles</p> </div> <p>Protective goggles and facial protection - Classification according to EN 166</p>
<p>- Body protection:</p>	<p>Protective work clothing protective clothing (EN 13034)</p>

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

<p>- General Information</p>	<p>According to product specification</p>
<p>- Colour:</p>	<p>Characteristic</p>
<p>- Odour:</p>	<p>Not determined.</p>
<p>- Odour threshold:</p>	<p>Undetermined.</p>
<p>- Melting point/freezing point:</p>	<p>130 °C</p>
<p>- Boiling point or initial boiling point and boiling range</p>	<p>Not applicable.</p>
<p>- Flammability</p>	<p>Not applicable.</p>
<p>- Lower and upper explosion limit</p>	<p>Not determined.</p>
<p>- Lower:</p>	<p>Not determined.</p>
<p>- Upper:</p>	<p>41 °C</p>
<p>- Flash point:</p>	<p>Not determined.</p>
<p>- Decomposition temperature:</p>	<p>Not determined.</p>
<p>- pH</p>	<p>Not determined.</p>
<p>- Viscosity:</p>	<p>90 mm²/s</p>
<p>- Kinematic viscosity at 20 °C</p>	<p>Not determined.</p>
<p>- Dynamic:</p>	<p>Not miscible or difficult to mix.</p>
<p>- Solubility</p>	<p>Not determined.</p>
<p>- water:</p>	<p>Not determined.</p>
<p>- Partition coefficient n-octanol/water (log value)</p>	<p>0.94 g/cm³</p>
<p>- Density and/or relative density</p>	<p>Not determined.</p>
<p>- Density at 20 °C:</p>	<p>Not determined.</p>
<p>- Relative density</p>	<p>Not determined.</p>
<p>- Vapour density</p>	<p>Not determined.</p>

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

Trade name: **KEMPERDUR Finish silk**

(Contd. of page 4)

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Solvent separation test:**
- **VOC (EC)** 54.00 %
- **Change in condition**
- **Evaporation rate** Not determined.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Flammable liquid and vapour.
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with water.
- **10.4 Conditions to avoid** Keep away from open flames/heat sources.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

Trade name: **KEMPERDUR Finish silk**

(Contd. of page 5)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

- **LD/LC50 values relevant for classification:**
53880-05-0 Isophorondiisocyanate homopolymer

Oral LD50 >14,000 mg/kg (rat) (OECD 401)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >3,160 mg/kg (rabbit) (OECD 402)

128601-23-0 Aromatic hydrocarbons, C9

Oral LD50 3,592 mg/kg (rat)

Dermal LD50 >3,160 mg/kg (rabbit)

Inhalative LC50/4 h >6,193 mg/l (rat)

140921-24-0 1,6-hexanediy-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Inhalative LC50/4 h 0.05 mg/l (ATE)

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Oral LD50 3,230 mg/kg (rat) (OECD-guideline 423)

Dermal LD50 >3,170 mg/kg (rat) (OECD Guideline 402 (Acute Dermal Toxicity))

77-58-7 dibutyltin dilaurate

Oral LD50 2,071 mg/kg (rat) (equivalent or similar to OECD 401; Sarasin, G. 1981)

123-05-7 2-ethylhexanal

Oral LD50 3,730 mg/kg (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**- **Aquatic toxicity:**
53880-05-0 Isophorondiisocyanate homopolymer

LC50/96 h >1.51 mg/l (Cyprinus Carpio) (Richtlinie 67/548/EWG, Anhang V, C.1.)

EC50 >3.36 mg/l (Daphnia magna) (OECD 202)

EC50 >10,000 mg/l (Belebtschlamm) (OECD 209)

64742-95-6 Solvent naphtha (petroleum), light arom.

LL 50 9.2 mg/l (fish) (96h; OECD 203)

EC50 3.2 mg/l (Daphnia magna) (48h; OECD 202)

EC50 2.6 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)

140921-24-0 1,6-hexanediy-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

LC50/96 h 316 mg/l (Danio rerio (Zebrabärbling)) (OECD 203)

EC50 1.77 mg/l (Bakterien) (activated sludge; ISO 8192-1986 E)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

Trade name: **KEMPERDUR Finish silk**

(Contd. of page 6)

IC50	43 mg/l (DESMODESMUS SUBSPICATUS) (72h; OECD 201)
EC50	193 mg/l (Daphnia magna) (48h; OECD 202)
1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
EC50	0.42 mg/l (ALGAE) (OECD 201)
LC50	0.9 mg/l /72 h (fish) (OECD 203 (96 hr))
77-58-7 dibutyltin dilaurate	
EC50	3.1 mg/l (Brachydanio rerio (Ricefish)) >2 mg/l (DESMODESMUS SUBSPICATUS) (72h) 1 mg/l (Scenedesmus subspicatus) 0.463 mg/l (Daphnia magna) (OECD 202)
LC 50	2 mg/l (Leuciscus idus (Goldorfe)) (48h)
LC20	2 mg/l (Leuciscus idus (Goldorfe)) (48h)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal according to official regulations

- European waste catalogue

08 05 01*	waste isocyanates
15 01 10*	packaging containing residues of or contaminated by hazardous substances
17 02 03	plastic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1866
- **14.2 UN proper shipping name**
- **ADR** 1866 RESIN SOLUTION, ENVIRONMENTALLY HAZARDOUS
- **IMDG** RESIN SOLUTION, MARINE POLLUTANT
- **IATA** RESIN SOLUTION

- 14.3 Transport hazard class(es)

- **ADR**



- **Class** 3 (F1) Flammable liquids.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

Trade name: **KEMPERDUR Finish silk**

(Contd. of page 7)

- Label 3

- IMDG



- Class 3 Flammable liquids.

- Label 3

- IATA



- Class 3 Flammable liquids.

- Label 3

- 14.4 Packing group III

- ADR, IMDG, IATA

- 14.5 Environmental hazards: Product contains environmentally hazardous substances: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

- Marine pollutant: Yes
Symbol (fish and tree)

- Special marking (ADR): Symbol (fish and tree)

- 14.6 Special precautions for user Warning: Flammable liquids.

- Hazard identification number (Kemler code): 30

- EMS Number: F-E,S-E

- Stowage Category A

- 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

- Transport/Additional information:

- ADR
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- Transport category 3
- Tunnel restriction code D/E

- IMDG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- UN "Model Regulation": UN 1866 RESIN SOLUTION, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20, 74

- Regulation (EU) No 649/2012

77-58-7 dibutyltin dilaurate

Annex I Part 1

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

Trade name: **KEMPERDUR Finish silk**

(Contd. of page 8)

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H361 Suspected of damaging fertility or the unborn child.
- H361f Suspected of damaging fertility.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction.

- Department issuing SDS:

research & development

- Contact:

research & development

- Date of previous version:

01.02.2022

- Version number of previous version:

5

- Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 1: Acute toxicity – Category 1
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1C: Skin corrosion/irritation – Category 1C
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Resp. Sens. 1: Respiratory sensitisation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- Skin Sens. 1B: Skin sensitisation – Category 1B
- Muta. 2: Germ cell mutagenicity – Category 2
- Repr. 1B: Reproductive toxicity – Category 1B
- Repr. 2: Reproductive toxicity – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2022

Version number 6 (replaces version 5)

Revision: 18.07.2022

Trade name: KEMPERDUR Finish silk

(Contd. of page 9)

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- Sources

- www.echa.europa.eu

- www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:

- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp

- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * Data compared to the previous version altered.

IE