Version number 13 (replaces version 12)

Revision: 26.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier	
- Trade name:	KEMCO 1K-Primer
- UFI:	RXP6-10GH-H00C-YTGR
 1.2 Relevant identified uses of the 	
substance or mixture and uses advised	
against	Identified use: intended for professional use only!
 Application of the substance / the mixture 	Primer
- 1.3 Details of the supplier of the safety data	sheet
- Manufacturer/Supplier:	KEMPER SYSTEM GmbH & Co. KG Holländische Strasse 32-36 34246 Vellmar Deutschland / Germany Telefon: +49 (0)561 / 8295-0 Telefax: +49 (0)561 / 8295-5110 E-Mail: MSDS@KEMPER-SYSTEM.COM
- Further information obtainable from: - 1.4 Emergency telephone number:	research & development Medical Emergency information in case of poisoning: Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240 (advisory service in German or English language)

SECTION 2: Hazards identification

S KEMPER SYSTEM

Printing date 26.08.2022

- 2.1 Classification of the substance or mixtu - Classification according to Regulation (EC)	
Flam. Liq. 3 H226 Flammable liqu	uid and vapour.
Eye Irrit. 2 H319 Causes serious	s eye irritation.
Skin Sens. 1 H317 May cause an a	allergic skin reaction.
STOT SE 3 H335-H336 May cause res	piratory irritation. May cause drowsiness or dizziness.
	swallowed and enters airways.
	c life with long lasting effects.
- 2.2 Label elements	\$\$\$
- Labelling according to Regulation (EC) No	
1272/2008	The product is classified and labelled according to the CLP regulation.
- Hazard pictograms	
	GHS02 GHS07 GHS08 GHS09
- Signal word	Danger
- Hazard-determining components of	
labelling:	Solvent naphtha (petroleum), light arom.
5	Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-
	methylbenzene
	Isophorondiisocyanate homopolymer hydrocarbons, C9, aromatic
	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate
	m-tolylidene diisocyanate
	hexahydromethylphthalic anhydride
	dibutyItin dilaurate
- Hazard statements	2-ethylhexanal H226 Flammable liquid and vapour.
	H319 Causes serious eye irritation.
	H317 May cause an allergic skin reaction.
	H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
	H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements	 H411 Toxic to aquatic life with long lasting effects. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
r reductionary statements	smoking.
	P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
	P405 Store locked up.
	P501 Dispose of contents/container in accordance with local/regional/national/international
	regulations. (Contd. on page 2



Version number 13 (replaces version 12)

Trade name: KEMCO 1K-Primer

- Additional information:

- 2.3 Other hazards

Printing date 26.08.2022

EUH204 Contains isocyanates. May produce an allergic reaction.

- Results of PBT and vPvB assessment

- PBT: - vPvB:

Not applicable. Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures		
- Description:	Mixture: consisting of the following components.	
- Dangerous componen		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	25-50%
EINECS: 265-199-0	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	
CAS: 37273-56-6	Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene	25-50%
EC number: 609-378-7	Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 53880-05-0	Isophorondiisocyanate homopolymer	2.5-10%
EC number: 931-312-3	Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 140921-24-0	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate	2.5-10%
ELINCS: 411-700-4	Skin Sens. 1, H317	
EC number: 918-668-5	hydrocarbons, C9, aromatic	≥0.5-<2.5%
	Flam. Lig. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	
CAS: 77-58-7	dibutyltin dilaurate	≥0.25-<0.3%
EINECS: 201-039-8	Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; Skin Corr. 1C, H314; Aquatic Acute 1,	
	H400; Aquatic Chronic 1, H410; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 25550-51-0	hexahydromethylphthalic anhydride	≥0.1-<0.5%
EINECS: 247-094-1	Resp. Sens. 1, H334; Eye Dam. 1, H318; Skin Sens. 1, H317	
CAS: 123-05-7	2-ethylhexanal	≥0.1-<0.5%
EINECS: 204-596-5	Flam. Liq. 3, H226; Repr. 2, H361; Skin Sens. 1B, H317	
CAS: 4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	<0.1%
EINECS: 223-861-6	Acute Tox. 1, H330; Resp. Sens. 1, H334; Áquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin	
	Sens. 1, H317; STOT SE 3, H335, EUH204	
	Specific concentration limits: Resp. Sens. 1; H334: $C \ge 0.5$ %	
	Skin Sens. 1; H317: C ≥ 0.5 %	
CAS: 26471-62-5	m-tolylidene diisocyanate	<0.1%
EINECS: 247-722-4	Acute Tox. 2, H330; Resp. Sens. 1, H334; Carc. 2, H351; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;	1
	STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204	
	Specific concentration limit: Resp. Sens. 1; H334: C \ge 0.1 %	
- SVHC		
25550-51-0 hexahvdro	methylphthalic anhydride	
- Additional information		

SECTION 4: First aid measures

 - 4.1 Description of first aid measures 	
- General information:	Immediately remove any clothing soiled by the product.
	Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48
	hours after the accident.
	Do not leave affected persons unattended.
	Personal protection for the First Aider.
	Take affected persons out of danger area and lay down.
- After inhalation:	In case of unconsciousness place patient stably in side position for transportation.
	Supply fresh air; consult doctor in case of complaints.
 After skin contact: 	Immediately wash with water and soap and rinse thoroughly.
	Seek medical treatment in case of complaints.
- After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
	Protect unharmed eye.
 After swallowing: 	If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects,	
both acute and delayed	No further relevant information available.
-	(Contd. on page 3)

Revision: 26.08.2022

(Contd. of page 1)

S KEMPER SYSTEM

Version number 13 (replaces version 12)

Revision: 26.08.2022

Trade name: KEMCO 1K-Primer

- 4.3 Indication of any immediate medical attention and special treatment needed	No further relevant information available.	(Contd. of page 2)
SECTION 5: Firefighting measures		
 - 5.1 Extinguishing media - Suitable extinguishing agents: 	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.	
- For safety reasons unsuitable extinguishing agents: - 5.2 Special hazards arising from the	Water with full jet	
substance or mixture	Formation of toxic gases is possible during heating or in case of fire.	

Nitrogen oxides (NOx) Carbon monoxide (CO) - 5.3 Advice for firefighters - Protective equipment: Do not inhale explosion gases or combustion gases. - Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures		
- 6.1 Personal precautions, protective		
equipment and emergency procedures	Wear protective equipment. Keep unprotected persons away.	
	Ensure adequate ventilation	
	Keep away from ignition sources.	
	Avoid contact with skin and eyes	
- 6.2 Environmental precautions:	Inform respective authorities in case of seepage into water course or sewage system.	
	Do not allow to enter sewers/ surface or ground water.	
	Prevent from spreading (e.g. by damming-in or oil barriers).	
- 6.3 Methods and material for containment		
and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
	Dispose contaminated material as waste according to item 13.	
	Do not flush with water or aqueous cleansing agents	
- 6.4 Reference to other sections	See Section 7 for information on safe handling.	
	See Section 8 for information on personal protection equipment.	
	See Section 13 for disposal information.	

ECTION 7: Handling and storage	
1 Precautions for safe handling	Store in cool, dry place in tightly closed receptacles. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
formation about fire - and explosion	
otection:	Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
2 Conditions for safe storage, including a	ny incompatibilities
orage:	
equirements to be met by storerooms and	I
ceptacles:	Store only in the original receptacle.
formation about storage in one common	
orage facility:	Store away from foodstuffs.
irther information about storage	
onditions:	Protect from frost.
	Store in dry conditions.
	Keep container tightly sealed.
	Recommended storage temperature: 5-30 °C
orage class:	3
3 Specific end use(s)	No further relevant information available.

(Contd. on page 4)

Printing date 26.08.2022





Printing date 26.08.2022

Safety data sheet according to 1907/2006/EC, Article 31

Version number 13 (replaces version 12)

Revision: 26.08.2022

Trade name: KEMCO 1K-Primer

	(Contd. of page 3)
SECTION 8: Exposure controls/pers	sonal protection
- 8.1 Control parameters	
- Ingredients with limit values that require mo	nitoring at the workplace:
77-58-7 dibutyltin dilaurate	
OEL Short-term value: 0.2 mg/m ³ Long-term value: 0.1 mg/m ³ as Sn	
4098-71-9 3-isocyanatomethyl-3,5,5-trimethyl	lcyclohexyl isocyanate
OEL Long-term value: 0.005 ppm Sens	
26471-62-5 m-tolylidene diisocyanate	
OEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ as -NCO; Sens.	
 Regulatory information Additional information: 	OEL: 2021 CoP for the Safety, Health and Welfare at Work The lists valid during the making were used as basis.
- 8.2 Exposure controls	No further data: and item 7
 Appropriate engineering controls Individual protection measures, such as per 	No further data; see item 7. sonal protective equipment
- General protective and hygienic measures:	The usual precautionary measures are to be adhered to when handling chemicals.
	Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing
	Wash hands before breaks and at the end of work.
- Respiratory protection:	Avoid contact with the eyes and skin. When used properly and under normal conditions, breathing protection is not required. Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2
- Hand protection	Respiratory protection - Gas filters and combination filters according to (DIN EN 141)
	Protective gloves Only use chemical-protective gloves with CE-labelling of category III. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Check protective gloves prior to each use for their proper condition. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation After use of gloves apply skin-cleaning agents and skin cosmetics.
- Material of gloves	Recommended materials: Butyl rubber, BR Recommended thickness of the material: ≥ 0.5 mm Penetration time (min.): < 480 The selection of the suitable gloves does not only depend on the material, but also on further marks of
- Penetration time of glove material	quality and varies from manufacturer to manufacturer. The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.
 As protection from splashes gloves made of the following materials are suitable: 	
- Eye/face protection	Tightly sealed goggles
- Body protection:	Protective goggles and facial protection - Classification according to EN 166 protective clothing (EN 13034)

(Contd. on page 5)



Printing date 26.08.2022

Safety data sheet according to 1907/2006/EC, Article 31

Version number 13 (replaces version 12)

Revision: 26.08.2022

Trade name: KEMCO 1K-Primer

(Contd. of page 4)

SECTION 9: Physical and chemica	Inconcretion	
SECTION 9. Physical and chemica	i properties	
- 9.1 Information on basic physical and che	nical properties	
- General Information		A constitute to product operation
- Colour: - Odour:		According to product specification
- Odour: - Odour threshold:		Characteristic Not determined.
- Melting point/freezing point:		Undetermined.
- Boiling point or initial boiling point and bo	iling range	155 °C
- Flammability	ining range	Not applicable.
- Lower and upper explosion limit		Not applicable.
- Lower:		Not determined.
- Upper:		Not determined.
- Flash point:		39 °C
- Decomposition temperature:		Not determined.
- pH		Not determined.
- Viscosity:		
 Kinematic viscosity at 20 °C 		46 mm²/s
- Dynamic:		Not determined.
- Solubility		
- water:		Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log v	alue)	Not determined.
 Density and/or relative density 		
- Density at 20 °C:		0.97 g/cm ³
- Relative density		Not determined.
- Vapour density		Not determined.
- 9.2 Other information		
- Appearance:		
- Form:		Fluid
- Important information on protection of hea	alth and environment, and o	n
safety.		
 Auto-ignition temperature: 		Product is not selfigniting.
 Explosive properties: 		Product is not explosive. However, formation of explosive air/vapour mixtures
.		are possible.
- Solvent separation test:		
- VOC (EC)		43.90 %
- Change in condition		N <i>i i i i</i>
- Evaporation rate		Not determined.
- Information with regard to physical hazard	classes	
- Explosives		
-	Void	
- Flammable gases	Void	
Aaraaala	Void	
- Aerosols	Void	
	Void	
- Oxidising gases	Void	
- Gases under pressure	volu	
- Gases under pressule		
	Void	
- Flammable liquids		
	Flammable liquid and vapo	bu r .
- Flammable solids		
	Void	
- Self-reactive substances and mixtures		
	Void	
- Pyrophoric liquids		
	Void	
 Pyrophoric solids 		
	Void	
		(Contd. on page



Version number 13 (replaces version 12)

Printing date 26.08.2022

Revision: 26.08.2022

Page 6/10

Trade name: KEMCO 1K-Primer

		(Contd. of page 5)
- Self-heating substances and mi	xtures	
- Substances and mixtures, whic water	Void n emit flammable gases in contact with	
	Void	
- Oxidising liquids	Void	
- Oxidising solids	Void	
- Organic peroxides	Void	
- Corrosive to metals		
- Desensitised explosives	Void	
	Void	

SECTION 10: Stability and reactivit	y
- 10.1 Reactivity - 10.2 Chemical stability - Thermal decomposition / conditions to be	No further relevant information available.
 avoided: 10.3 Possibility of hazardous reactions 	No decomposition if used and stored according to specifications. Reacts with water and acids.
	Reacts with amines. Reacts with water
- 10.4 Conditions to avoid	Reacts with humid air. No further relevant information available.
 10.5 Incompatible materials: 10.6 Hazardous decomposition products: 	Amines, acids, alkalis, strong oxidants, alcohols No dangerous decomposition products known.

SECTION 11: Toxicological information

- Acute to		n hazard classes as defined in Regulation (EC) No 1272/2008 Based on available data, the classification criteria are not met.	
- LD/LC50	values re	levant for classification:	
64742-95	-6 Solven	t naphtha (petroleum), light arom.	
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)	
37273-56	-6 Poly[o	ky(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene	
Oral	LD50	>5,000 mg/kg (rat)	
53880-05	-0 Isopho	rondiisocyanate homopolymer	
Oral	LD50	>14,000 mg/kg (rat) (OECD 401)	
140921-2	4-0 1,6-he	xanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate	
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
hydrocar	bons, C9,	aromatic	
Oral	LD50	>3,492 mg/kg (rat) (OECD 401)	
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)	
77-58-7 d	libutyltin (dilaurate	
Oral	LD50	2,071 mg/kg (rat) (eqivalent or similar to OECD 401; Sarasin, G. 1981)	
25550-51	-0 hexahy	dromethylphthalic anhydride	
Oral	LD50	>5,000 mg/kg (rat)	
123-05-7	2-ethylhe	xanal	
Oral	LD50	3,730 mg/kg (rat)	
		(Co	ntd. on page 7



Version number 13 (replaces version 12)

Revision: 26.08.2022

Trade name: KEMCO 1K-Primer

Printing date 26.08.2022

			(Contd. of page 6)
4098-71-9 3-isocya	natomethyl-3,5,5-trimet	hylcyclohexyl isocyanate	
Inhalative LC50/4 h	n 0.05 mg/l (ATE)		
26471-62-5 m-tolyl	idene diisocyanate		
Oral LD50	5,110 mg/kg (rat)		
Inhalative LC50/4 h	n 0.107 mg/l (rat)		
LC50/1 h	n 0.47 mg/l (rat)		
- Skin corrosion/irri	tation	Based on available data, the classification criteria are not met.	
 Serious eye damag 		Causes serious eye irritation.	
 Respiratory or skin 		May cause an allergic skin reaction.	
 Germ cell mutager 	nicity	Based on available data, the classification criteria are not met.	
 Carcinogenicity 		Based on available data, the classification criteria are not met.	
 Reproductive toxic 	2	Based on available data, the classification criteria are not met.	
- STOT-single exposed		May cause respiratory irritation. May cause drowsiness or dizziness.	
 STOT-repeated expl 	posure	Based on available data, the classification criteria are not met.	
- Aspiration hazard		May be fatal if swallowed and enters airways.	
- 11.2 Information o			
 Endocrine disrupt 	ing properties		
None of the ingredie	ents is listed.		

SECTION 12: Ecological information

- 12.1 Tox	icity		
- Aquatic	toxicity:		
64742-9	5-6 Solvent naphtha (petroleum), I	ight arom.	
LL 50	9.2 mg/l (fish) (96h; OECD 203)		
EC50	3.2 mg/l (Daphnia magna) (48h; (DECD 202)	
EC50	2.6 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)		
37273-56	6-6 Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene	
EC50	>10,000 mg/l (Belebtschlamm) (C	DECD 209)	
	5-0 Isophorondiisocyanate homop	•	
LC50/96	h >1.51 mg/l (Cyprinus Carpio) (Ric	htlinie 67/548/EWG, Anhang V, C.1.)	
EC50	>3.36 mg/l (Daphnia magna) (OE	CD 202)	
EC50	>10,000 mg/l (Belebtschlamm) (C	DECD 209)	
		/Ipentyl)-3-oxazolidinyl)ethyl)carbamate	
	h 316 mg/l (Danio rerio (Zebrabärbl		
EC50	1.77 mg/l (Bakterien) (activated sludge; ISO 8192-1986 E)		
IC50	43 mg/l (DESMODESMUS SUBSPICATUS) (72h; OECD 201)		
EC50	193 mg/l (Daphnia magna) (48h; OECD 202)		
•	rbons, C9, aromatic		
LL 50	9.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h; OECD 203)		
EL50	2.9 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)		
	3.2 mg/l (Daphnia magna) (48h; OECD 202)		
EC50	>99 mg/l (Belebtschlamm) (10 min.; OECD 209)		
77-58-7	dibutyltin dilaurate		
EC50	3.1 mg/l (Brachydanio rerio (Rice	íish))	
	>2 mg/l (DESMODESMUS SUBS		
	1 mg/l (Scenedesmus subspicatu	s)	
	0.463 mg/l (Daphnia magna) (OE	CD 202)	
LC 50	2 mg/l (Leuciscus idus (Goldorfe)) (48h)		
LC20	2 mg/l (Leuciscus idus (Goldorfe)) (48h)	
	sistence and degradability	No further relevant information available.	
	accumulative potential	No further relevant information available.	
	bility in soil sults of PBT and vPvB assessmen	No further relevant information available.	
- 12.5 Res - PBT:	Buits of FDT and VFVD assessmen	Not applicable.	
- vPvB:		Not applicable.	
- 12.6 Enc	locrine disrupting properties	The product does not contain substances with endocrine disrupting properties.	(Contd. on page 8)





Version number 13 (replaces version 12)

Revision: 26.08.2022

Trade name: KEMCO 1K-Primer

Printing date 26.08.2022

		(Contd. of page 7)
 12.7 Other adverse effects Remark: Additional ecological information: 	Toxic for fish	
- General notes:	Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms	
SECTION 13: Disposal consider	ations	

- 13.1 Wast - Recomme	e treatment methods Indation	Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal according to official regulations
- European	waste catalogue	
08 05 01*	waste isocyanates	
15 01 10*	packaging containing residues of or contaminated by hazardous substances	
17 02 03	plastic	
	- Uncleaned packaging: - Recommendation: Disposal must be made according to official regulations.	

SECTION 14: Transport information	
- 14.1 UN number or ID number - ADR, IMDG, IATA	UN1866
- 14.2 UN proper shipping name - ADR - IMDG - IATA	1866 RESIN SOLUTION, ENVIRONMENTALLY HAZARDOUS RESIN SOLUTION, MARINE POLLUTANT RESIN SOLUTION
- 14.3 Transport hazard class(es) - ADR	
- Class - Label	3 (F1) Flammable liquids. 3
- IMDG	
- Class	3 Flammable liquids.
- Label	3
- IATA	
- Class	3 Flammable liquids.
- Label	3
- 14.4 Packing group - ADR, IMDG, IATA	111
- 14.5 Environmental hazards: - Marine pollutant:	Product contains environmentally hazardous substances: dibutyltin dilaurate Yes Symbol (fish and tree)
	(Contd. on page 9)





according to 1907/2006/EC, Article 31

Version number 13 (replaces version 12)

Revision: 26.08.2022

Trade name: KEMCO 1K-Primer

Printing date 26.08.2022

	(Contd. of page 8)
- Special marking (ADR):	Symbol (fish and tree)
- 14.6 Special precautions for user - Hazard identification number (Kemler code): - EMS Number: - Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
- 14.7 Maritime transport in bulk according to IMO instrumer	nts Not applicable.
- Transport/Additional information:	
- ADR - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- Transport category - Tunnel restriction code	3 D/E
- Tunnel restriction code - IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information - 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU	
 Named dangerous substances - ANNEX I 	None of the ingredients is listed.
 Seveso category 	E2 Hazardous to the Aquatic Environment
	P5c FLAMMABLE LIQUIDS
 Qualifying quantity (tonnes) for the 	
application of lower-tier requirements	200 t
- Qualifying quantity (tonnes) for the	
application of upper-tier requirements	500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII	Conditions of rootriction: 2, 20, 74
	Conditions of restriction: 3, 20, 74
- Regulation (EU) No 649/2012	· · · · · · · · · · · · · · · · · · ·
77-58-7 dibutyltin dilaurate	Annex I Part 1
	f the use of certain hazardous substances in electrical and electronic equipment – Annex II
None of the ingredients is listed.	
- REGULATION (EU) 2019/1148	
- Annex I - RESTRICTED EXPLOSIVES PREC	CURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.	
- Annex II - REPORTABLE EXPLOSIVES PRE	CURSORS
None of the ingredients is listed.	
- Regulation (EC) No 273/2004 on drug precu	irsors
108-88-3 toluene	3
- Regulation (EC) No 111/2005 laying down r	ules for the monitoring of trade between the Community and third countries in drug precursors
108-88-3 toluene	3
- National regulations:	
- Other regulations, limitations and prohibiti	ve regulations
- Substances of very high concern (SVHC) a	0 <i>i</i>
25550-51-0 hexahydromethylphthalic anhydrid	de
- 15.2 Chemical safety assessment:	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

L

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878. (Contd. on page 10)



Page 10/10

ΙE

Safety data sheet according to 1907/2006/EC, Article 31

Version number 13 (replaces version 12)

Printing date 26.08.2022

Trade name: KEMCO 1K-Primer

Revision: 26.08.2022

	 H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction.
	 H318 Causes serious eye damage. H319 Causes serious eye irritation. H330 Fatal if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H341 Suspected of causing genetic defects. H351 Suspected of causing cancer. H360FD May damage fertility. May damage the unborn child. H370 Causes damage to organs. H372 Causes damage to organs. H372 Causes damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. EUH204 Contains isocyanates. May produce an allergic reaction.
 Contact: Date of previous version: Version number of previous version: Abbreviations and acronyms: 	research & development research & development 06.05.2022 12 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) MDG: International Maritime Code for Dangerous Goods ATA: International Maritime Code for Dangerous Goods Code System of Classification and Labelling of Chemicals EINECS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal cose, 50 percent D40: vol Presistent and very Bioaccumulative Film. Lig: 3: Flammable liquids – Category 1 Acute Tox: 1: Acute toxicity – Category 1 Acute Tox: 1: Acute toxicity – Category 2 Swin Corr. 1C: Skin corrosion/irritation – Category 1 Skin Irrit. 2: Skin corrosion/irritation – Category 1 Skin Sens. 1: Respiratory sensitisation – Category 2 Carc. 2: Carcinogenicity – Category 1 Skin Sens. 1: Respiratory costeny 1 Aquatic Acute 1: Hazardous to the aquatic environment - Long-term aquatic hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment -
- Sources	Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 - www.echa.europa.eu - www.baua.de IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance: - www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp - www.dguv.de/ifa/gestis/gestis-dnel-liste

altered.