

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 9 (replaces version 8) Revision: 16.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: KEMPERTEC AC Primer
- UFI: TAVA-SONS-3005-T8NY

- 1.2 Relevant identified uses of the

substance or mixture and uses advised

against Identified use: intended for professional use only!
 Application of the substance / the mixture
 Primer

- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: KEMPER SYSTEM GmbH & Co. KG

Holländische Strasse 32-36

34246 Vellmar

Deutschland / Germany Telefon: +49 (0)561 / 8295-0 Telefax: +49 (0)561 / 8295-5110 E-Mail: MSDS@KEMPER-SYSTEM.COM

- Further information obtainable from: research & development

- **1.4 Emergency telephone number:** Medical Emergency information in case of poisoning:

Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240

(advisory service in German or English language)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

- 2.2 Label elements

 Labelling according to Regulation (EC) No 1272/2008

- Hazard pictograms

The product is classified and labelled according to the CLP regulation.





_

P405

- **Signal word** Danger

- Hazard-determining components of

labelling:

methyl methacrylate

tetramethylene dimethacrylate

2-ethylhexyl acrylate

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-

methylphenyl)amino]-

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

- **Precautionary statements** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower]. Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- 2.3 Other hazards

- Hazard statements

- Results of PBT and vPvB assessment

- PBT: Not applicable.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 9 (replaces version 8) Revision: 16.11.2023

Trade name: KEMPERTEC AC Primer

- vPvB: Not applicable. (Contd. of page 1)

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- Description: Mixture: consisting of the following components.

- Dangerous components:				
CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-100%		
CAS: 2082-81-7 EINECS: 218-218-1	tetramethylene dimethacrylate Skin Sens. 1B, H317	2.5-10%		
CAS: 103-11-7 EINECS: 203-080-7	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥1-<2.5%		
	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl) amino]- Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%		

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours

after the accident.

Do not leave affected persons unattended. Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints. Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eve.

- After swallowing: - 4.2 Most important symptoms and effects,

both acute and delayed

After skin contact:

- 4.3 Indication of any immediate medical attention and special treatment needed

If symptoms persist consult doctor.

No further relevant information available

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing

5.2 Special hazards arising from the

substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NOx) Carbon monoxide (CÓ)

Water with full jet

- 5.3 Advice for firefighters

- Protective equipment: Do not inhale explosion gases or combustion gases.

- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 3)





according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 9 (replaces version 8) Revision: 16.11.2023

Trade name: KEMPERTEC AC Primer

(Contd. of page 2)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective

equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation Keep away from ignition sources.

- **6.2 Environmental precautions:** Prevent from spreading (e.g. by damming-in or oil barriers).

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment

and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Do not flush with water or aqueous cleansing agents

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles. Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire - and explosion

protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

Storage

- Requirements to be met by storerooms and

receptacles:

Store only in the original receptacle.

- Information about storage in one common

storage facility:

- Further information about storage

conditions:

Store away from foodstuffs.

Protect from frost. Store in dry conditions. Keep container tightly sealed.

Recommended storage temperature: 5-30 °C

- Storage class:

- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

OEL Short-term value: 100 ppm Long-term value: 50 ppm

IOELV, Sens

Regulatory information
 Additional information:
 OEL: 2021 CoP for the Safety, Health and Welfare at Work
 The lists valid during the making were used as basis.

- 8.2 Exposure controls

Appropriate engineering controls
 Individual protection measures, such as personal protective equipment

- General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection: When used properly and under normal conditions, breathing protection is not required.

Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 9 (replaces version 8) Revision: 16.11.2023

Trade name: KEMPERTEC AC Primer

(Contd. of page 3)

Filter A/P2

Respiratory protection - Gas filters and combination filters according to (EN 14387)

- Hand protection



Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the

Check protective gloves prior to each use for their proper condition.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time (min.): < 480

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

and varies from manufacturer to manufacturer.

- Penetration time of glove material The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions.

- As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.1 mm

Penetration time (min.): < 10

- Eye/face protection

Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166

- Body protection: protective clothing (EN 13034)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Colour: - Odour:

- Odour threshold:

- Melting point/freezing point: Undetermined - Boiling point or initial boiling point and boiling range 101 °C

Not applicable.

Colourless

Characteristic

Not determined.

- Flammability

- Lower and upper explosion limit

Not determined.

- Lower: - Upper:

Not determined.

- Flash point:

10 °C

- Decomposition temperature:

Not determined

- pH

Not determined.

- Viscosity: - Kinematic viscosity at 20 °C

250 mm²/s

- Dynamic:

Not determined.

- Solubility

- water:

- Vapour density

Not miscible or difficult to mix.

- Partition coefficient n-octanol/water (log value)

Not determined.

- Density and/or relative density

0.99 g/cm³

- Density at 20 °C: - Relative density

Not determined. Not determined.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 9 (replaces version 8) Revision: 16.11.2023

Trade name: KEMPERTEC AC Primer

(Contd. of page 4)

- 9.2 Other information

- Appearance:

- Form: Fluid - Important information on protection of health and environment, and on

safety.

- Ignition temperature: Product is not selfigniting.

- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

Void

No decomposition if used according to specifications.

- Solvent separation test:

- VOC (EC) 6.30 % - Change in condition

- Evaporation rate Not determined.

- Information with regard to physical hazard classes

- Explosives Void - Flammable gases Void - Aerosols Void - Oxidising gases Void - Gases under pressure Void

- Flammable liquids Highly flammable liquid and vapour.

- Flammable solids Void - Self-reactive substances and mixtures Void - Pyrophoric liquids Void - Pyrophoric solids Void - Self-heating substances and mixtures Void

- Substances and mixtures, which emit flammable gases in contact with

water

Void Oxidising liquids Void - Oxidising solids Void - Organic peroxides Void - Corrosive to metals Void

- Desensitised explosives

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be

- 10.3 Possibility of hazardous reactions After the addition of catalysts, exothermic polymerisation might occur.

Reacts with peroxides.

- 10.4 Conditions to avoid No further relevant information available. - 10.5 Incompatible materials: No further relevant information available. - 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification: 80-62-6 methyl methacrylate

Oral LD50 >5,000 mg/kg (rat) Dermal LD50 >5,000 mg/kg (rabbit) Inhalative LC50/4 h 29.8 mg/l (rat)

2082-81-7 tetramethylene dimethacrylate

Oral LD50 10,066 mg/kg (rat) (OECD 401)

LD50 Dermal >3,000 mg/kg (rabbit)

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 9 (replaces version 8) Revision: 16.11.2023

Trade name: KEMPERTEC AC Primer

(Contd. of page 5) 103-11-7 2-ethylhexyl acrylate 4,435 mg/kg (rat) (IUCLID) Oral LD50 Dermal LD50 7,522 mg/kg (rabbit) (IUCLID) Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-Oral LD50 619 mg/kg (rat) (OECD 401) Dermal LD50 >2,000 mg/kg (rat) (OECD 402)

- Skin corrosion/irritation Causes skin irritation.

- Serious eye damage/irritation Based on available data, the classification criteria are not met. - Respiratory or skin sensitisation May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. - Carcinogenicity - Reproductive toxicity Based on available data, the classification criteria are not met.

- STOT-single exposure May cause respiratory irritation.

- STOT-repeated exposure Based on available data, the classification criteria are not met. - Aspiration hazard Based on available data, the classification criteria are not met.

- 11.2 Information on other hazards

- Endocrine disrupting properties

128-37-0 2,6-di-tert-butyl-p-cresol

List II

SECTIO	DN 12: Eco	logical i	nformation

- 12.1 Toxic	ity	
- Aquatic to	•	
80-62-6 m	ethyl metha	acrylate
	NOEC	37 mg/l (Daphnia magna) (21 days; OECD 202 Part 2, flow)
	EC3	37 mg/l (Scenedesmus quadricauda) (DIN 38412 Part 9; 8d)
	EC0	100 mg/l (Pseudomonas putida)
	EC50	69 mg/l (Daphnia magna) (48 h; OECD 202)
	LC 50	>79 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96 h; OECD 203)
	,	lene dimethacrylate
	EC50	9.79 mg/l (DESMODESMUS SUBSPICATUS) (72h; OECD 201)
		32.5 mg/l (Idus melanotus) (48h; OECD 203)
	NOEC	20 mg/l (Belebtschlamm)
	EC10	4.35 mg/l (DESMODESMUS SUBSPICATUS) (72d; OECD 201)
		7.51 mg/l (Daphnia magna) (21d; OECD 211)
103-11-7 2	ethylhexy	l acrylate
Inhalative	LC50/8h	1.19 mg/l (rat) (OECD 403)
	LC50/96 h	1.8 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
	EC50	17 mg/l (Daphnia magna) (48h; IUCLID)
	EC50	>10,000 mg/l (Pseudomonas putida) (30 min.; IUCLID)
	IC50	44 mg/l (DESMODESMUS SUBSPICATUS) (72h, IUCLID)
		23 mg/l (Leuciscus idus (Goldorfe)) (48h; IUCLID)
Reaction		'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-
	LC50/96 h	>100 mg/l (Cyprinus Carpio) (OECD 203 (96 hr))
	EC50	>100 mg/l (Scenedesmus subspicatus) (OECD 201; static)
	EC50	48 mg/l (Daphnia magna) (OECD 202; part 1 static)
	EC50	>100 mg/l (Cyprinus Carpio) (96h; OECD 203; ISO 7346; 92/69/CEE; C.1 static)
	NOEC	>100 mg/l (Scenedesmus subspicatus) (OECD 201, static)

 12.2 Persistence and degradability No further relevant information available. - 12.3 Bioaccumulative potential No further relevant information available. - 12.4 Mobility in soil No further relevant information available.

- 12.5 Results of PBT and vPvB assessment

Not applicable. - PBT: - vPvB: Not applicable.

(Contd. on page 7)

(Contd. of page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 9 (replaces version 8) Revision: 16.11.2023

Trade name: KEMPERTEC AC Primer

For information on endocrine disrupting properties see section 11.

- 12.6 Endocrine disrupting properties - 12.7 Other adverse effects

- Additional ecological information:

- General notes: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal according to official regulations

- European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

15 01 10* packaging containing residues of or contaminated by hazardous substances

17 02 03 plastic

- Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN number or ID number

- ADR, IMDG, IATA UN1993

- 14.2 UN proper shipping name

- ADR

1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED) - IMDG, IATA FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED)

- 14.3 Transport hazard class(es)

- ADR



 Class 3 (F1) Flammable liquids.

- Label

- IMDG, IATA



- Class 3 Flammable liquids.

- Label

- ADR, IMDG, IATA

- 14.4 Packing group

Ш

- 14.5 Environmental hazards:

- Marine pollutant: Nο

- 14.6 Special precautions for user Warning: Flammable liquids.

- Hazard identification number (Kemler code):

- EMS Number: F-E,S-E - Stowage Category

- 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

(Contd. on page 8)





according to 1907/2006/EC, Article 31

Printing date 16.11.2023 Version number 9 (replaces version 8) Revision: 16.11.2023

Trade name: KEMPERTEC AC Primer

(Contd. of page 7) - Transport/Additional information: - Limited quantities (LQ) 1L - Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml - Transport category - Tunnel restriction code D/E - IMDG - Limited quantities (LQ) 1L - Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml - UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category - Qualifying quantity (tonnes) for the

application of lower-tier requirements 5,000 t

- Qualifying quantity (tonnes) for the

application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX

XVII Conditions of restriction: 3

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

P5c FLAMMABLE LIQUIDS

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

108-88-3 toluene

- Regulation (EC) No 273/2004 on drug precursors

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

108-88-3 toluene

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

- Department issuing SDS: research & development - Contact: research & development

- Date of previous version: 29.06.2021

(Contd. on page 9)

3

3



(Contd. of page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 9 (replaces version 8) Printing date 16.11.2023 Revision: 16.11.2023

Trade name: KEMPERTEC AC Primer

- Version number of previous version:

- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- www.echa.europa.eu

- www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:

- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp

- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * Data compared to the previous version altered.

- Sources