Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **KEMPERDUR Deko Coating beige**
- **UFI:** 8XK8-R0P7-X00C-DAU2
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Identified use: intended for professional use only!
- **Application of the substance / the mixture** Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** KEMPER SYSTEM GmbH
Holländische Strasse 32-36
34246 Vellmar
Deutschland / Germany
Telefon: +49 (0)561 / 8295-0
Telefax: +49 (0)561 / 8295-5110
E-Mail: MSDS@KEMPER-SYSTEM.COM
- **Further information obtainable from:** research & development
- **1.4 Emergency telephone number:** Medical Emergency information in case of poisoning:
Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240
(advisory service in German or English language)

*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226 Flammable liquid and vapour.
Acute Tox. 4	H332 Harmful if inhaled.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
aliphatic polyisocyanate
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
Oligomerisation and alkylation reaction products of 2-phenylpropene and phenol
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate
Isophorondiisocyanate homopolymer
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
2-ethylhexanal
2-n-butyl-benzo[d]isothiazol-3-one
- **Hazard statements**
H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**
EUH204 Contains isocyanates. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
As from 24 August 2023 adequate training is required before industrial or professional use.

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

Trade name: KEMPERDUR Deko Coating beige

(Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

*

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture: consisting of the following components.

- **Dangerous components:**

CAS: 426822-87-9 EC number: 642-395-8	aliphatic polyisocyanate Skin Sens. 1, H317	25-50%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	10-12.5%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-10%
EC number: 700-960-7	Oligomerisation and alkylation reaction products of 2-phenylpropene and phenol Skin Irrit. 2, H315; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	≥2.5-<10%
CAS: 140921-24-0 ELINCS: 411-700-4	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate Skin Sens. 1, H317	2.5-10%
CAS: 53880-05-0 EC number: 931-312-3	Isophorondiisocyanate homopolymer Skin Sens. 1B, H317; STOT SE 3, H335	2.5-10%
EC number: 918-668-5	hydrocarbons, C9, aromatic Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	≥0.5-<2.5%
CAS: 4098-71-9 EINECS: 223-861-6	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.25%
CAS: 123-05-7 EINECS: 204-596-5	2-ethylhexanal Flam. Liq. 3, H226; Repr. 2, H361; Skin Sens. 1B, H317	≥0.1-<0.5%
CAS: 4299-07-4 ELINCS: 420-590-7	2-n-butyl-benzo[d]isothiazol-3-one Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≥0.1-<0.25%
CAS: 77-99-6 EINECS: 201-074-9	propylidynetrimethanol Repr. 2, H361fd	<0.5%
CAS: 1065336-91-5 EC number: 915-687-0	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.025-<0.1%

- **SVHC**

Oligomerisation and alkylation reaction products of 2-phenylpropene and phenol

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Do not leave affected persons unattended.
Personal protection for the First Aider.
Take affected persons out of danger area and lay down.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment in case of complaints.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Protect unharmed eye.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

Trade name: KEMPERDUR Deko Coating beige

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO_2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.
Nitrogen oxides (NOx)
Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
Prevent from spreading (e.g. by damming-in or oil barriers).
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Store in dry conditions.
Protect from frost.
Keep container tightly sealed.
Recommended storage temperature: 5-30 °C
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

Trade name: KEMPERDUR Deko Coating beige

(Contd. of page 3)

*

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**	
108-65-6 2-methoxy-1-methylethyl acetate	
OEL	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin, IOELV
4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	
OEL	Long-term value: 0.005 ppm Sens

- **Regulatory information** OEL: 2024 CoP for the Safety, Health and Welfare at Work
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:** The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:** When used properly and under normal conditions, breathing protection is not required.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2
Respiratory protection - Gas filters and combination filters according to (EN 14387)
- **Hand protection**

Protective gloves

Check protective gloves prior to each use for their proper condition.
Only use chemical-protective gloves with CE-labelling of category III.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves** Recommended materials:
Butyl rubber, BR
Recommended thickness of the material: ≥ 0.5 mm
Penetration time (min.): < 480
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material** The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.
- **As protection from splashes gloves made of the following materials are suitable:** Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.1 mm
Penetration time (min.): < 10
- **Eye/face protection**

Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166
- **Body protection:** protective clothing (EN 13034)

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

Trade name: KEMPERDUR Deko Coating beige

(Contd. of page 4)

- **Boiling point or initial boiling point and boiling range**	165 °C
- **Flammability**	Not applicable.
- **Lower and upper explosion limit**	
- **Lower:**	0.7 Vol %
- **Upper:**	7 Vol %
- **Flash point:**	36 °C
- **Auto-ignition temperature:**	315 °C
- **Decomposition temperature:**	Not determined.
- **pH**	Not determined.
- **Viscosity:**	
- **Kinematic viscosity at 20 °C**	106 s (ISO 6 mm)
- **Dynamic:**	Not determined.
- **Solubility**	
- **water:**	Not miscible or difficult to mix.
- **Partition coefficient n-octanol/water (log value)**	Not determined.
- **Density and/or relative density**	
- **Density at 20 °C:**	1.44 g/cm³
- **Relative density**	Not determined.
- **Vapour density**	Not determined.
- **9.2 Other information**	
- **Appearance:**	
- **Form:**	Fluid
- **Important information on protection of health and environment, and on safety.**	
- **Ignition temperature:**	Product is not selfigniting.
- **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Solvent separation test:**	
- **VOC (EC)**	23.40 %
- **Change in condition**	
- **Evaporation rate**	Not determined.
- **Information with regard to physical hazard classes**	
- **Explosives**	Void
- **Flammable gases**	Void
- **Aerosols**	Void
- **Oxidising gases**	Void
- **Gases under pressure**	Void
- **Flammable liquids**	Flammable liquid and vapour.
- **Flammable solids**	Void
- **Self-reactive substances and mixtures**	Void
- **Pyrophoric liquids**	Void
- **Pyrophoric solids**	Void
- **Self-heating substances and mixtures**	Void
- **Substances and mixtures, which emit flammable gases in contact with water**	Void
- **Oxidising liquids**	Void
- **Oxidising solids**	Void
- **Organic peroxides**	Void
- **Corrosive to metals**	Void
- **Desensitised explosives**	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity**	No further relevant information available.
- **10.2 Chemical stability**	
- **Thermal decomposition / conditions to be avoided:**	No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**	Reacts with alcohols, amines, aqueous acids and alkalis. Reacts with water.
- **10.4 Conditions to avoid**	No further relevant information available.
- **10.5 Incompatible materials:**	Amines, acids, alkalis, strong oxidants, alcohols

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

Trade name: KEMPERDUR Deko Coating beige

(Contd. of page 5)

- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

*

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

- **LD/LC50 values relevant for classification:**		
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
Oligomerisation and alkylation reaction products of 2-phenylpropene and phenol		
Oral	LD50	>2,000 mg/kg (rat) (OECD-guidline 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD Guideline 402 (Acute Dermal Toxicity))
Inhalative	LC50/4 h	>4.92 mg/l (rat) (OECD Guideline 403 (Acute Inhalation Toxicity))
140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
53880-05-0 Isophorondiisocyanate homopolymer		
Oral	LD50	>14,000 mg/kg (rat) (OECD 401)
hydrocarbons, C9, aromatic		
Oral	LD50	>3,492 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate		
Oral	LD50	4,814 mg/kg (rat) (OECD Guideline 401 (Acute Oral Toxicity))
Dermal	LD50	>7,000 mg/kg (rat) (OECD Guideline 402 (Acute Dermal Toxicity))
Inhalative	LC50/4 h	0.031 mg/l (rat) (OECD Guideline 403 (Acute Inhalation Toxicity))
123-05-7 2-ethylhexanal		
Oral	LD50	3,730 mg/kg (rat)
4299-07-4 2-n-butyl-benzo[d]isothiazol-3-one		
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
77-99-6 propylidynetrimethanol		
Oral	LD50	14,100 mg/kg (rat)
1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Oral	LD50	3,230 mg/kg (rat) (OECD-guidline 423)
Dermal	LD50	>3,170 mg/kg (rat) (OECD Guideline 402 (Acute Dermal Toxicity))

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**		
128-37-0	2,6-di-tert-butyl-p-cresol	List II
556-67-2	octamethylcyclotetrasiloxane	List II; III

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

Trade name: KEMPERDUR Deko Coating beige

(Contd. of page 6)

*

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**	
64742-95-6 Solvent naphtha (petroleum), light arom.	
LL 50	9.2 mg/l (fish) (96h; OECD 203)
EC50	3.2 mg/l (Daphnia magna) (48h; OECD 202)
EC50	2.6 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
108-65-6 2-methoxy-1-methylethyl acetate	
LC50/96 h	>100 mg/l (ricefish)
	161 mg/l (fish)
Oligomerisation and alkylation reaction products of 2-phenylpropene and phenol	
EC50	15 mg/l (DESMODESMUS SUBSPICATUS) (OECD 201)
	17 mg/l (Daphnia magna) (OECD 202 (48 hr))
	25.8 mg/l (zebrafish) (OECD 203 (96 hr))
140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate	
LC50/96 h	316 mg/l (zebrafish) (OECD 203)
EC50	1.77 mg/l (bacteria) (activated sludge; ISO 8192-1986 E)
IC50	43 mg/l (DESMODESMUS SUBSPICATUS) (72h; OECD 201)
EC50	193 mg/l (Daphnia magna) (48h; OECD 202)
53880-05-0 Isophorondiisocyanate homopolymer	
LC50/96 h	>1.51 mg/l (carp) (Richtlinie 67/548/EWG, Anhang V, C.1.)
EC50	>3.36 mg/l (Daphnia magna) (OECD 202)
EC50	>10,000 mg/l (animated mud) (OECD 209)
hydrocarbons, C9, aromatic	
LL 50	9.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h; OECD 203)
EL50	2.9 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
	3.2 mg/l (Daphnia magna) (48h; OECD 202)
EC50	>99 mg/l (animated mud) (10 min.; OECD 209)
4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	
EC50	>208 mg/l (carp)
	>70 mg/l (DESMODESMUS SUBSPICATUS)
	49 mg/l (Daphnia magna)
4299-07-4 2-n-butyl-benzo[d]isothiazol-3-one	
ErC50	0.45 mg/l (green algae) (72h)
LC50/96 h	0.15 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (OECD 203)
EC50	93 mg/l (Daphnia magna) (OECD 202)
1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
EC50	0.42 mg/l (alga) (OECD 201)
LC50	0.9 mg/l /72 h (fish) (OECD 203 (96 hr))

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

Trade name: KEMPERDUR Deko Coating beige

(Contd. of page 7)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal according to official regulations

- **European waste catalogue**	
08 05 01*	waste isocyanates
15 01 10*	packaging containing residues of or contaminated by hazardous substances
17 02 03	plastic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG** Void
- **IATA** UN1263

- **14.2 UN proper shipping name**
- **ADR, IMDG** Void
- **IATA** PAINT

- **14.3 Transport hazard class(es)**
- **ADR, ADN, IMDG**
- **Class** Void

- **IATA**

- **Class** 3 Flammable liquids.
- **Label** 3

- **14.4 Packing group**
- **ADR, IMDG** Void
- **IATA** III

- **14.5 Environmental hazards:**
- **Marine pollutant:** No

- **14.6 Special precautions for user** Not applicable.

- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

- **Transport/Additional information:**

- **ADR**
- **Remarks:**

Kein Gut der Kl. 3 gemäß 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code
ADR IMDG: Verpackung > 450 l = UN 1263 - Kl. 3 - Farbe - VPIII
Außerhalb ADR / IMDG = UN 1263 - Kl. 3 - Farbe - VPIII

Not goods of cl. 3 in accordance with 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code
ADR/IMDG: Packaging > 450 l = UN 1263 - Cl. 3 - Paint - PGIII
Outside ADR / IMDG = UN 1263 - Cl. 3 - Paint - PGIII

- **UN "Model Regulation":** Void

*

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

Trade name: KEMPERDUR Deko Coating beige

(Contd. of page 8)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 74

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**

- **Substances of very high concern (SVHC) according to REACH, Article 57**

Oligomerisation and alkylation reaction products of 2-phenylpropene and phenol

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- **Relevant phrases**

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H361f Suspected of damaging fertility.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH204 Contains isocyanates. May produce an allergic reaction.

- **Department issuing SDS:** research & development
- **Contact:** research & development
- **Date of previous version:** 01.02.2022
- **Version number of previous version:** 12
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.02.2025 Version number 13 (replaces version 12) Revision: 13.02.2025

Trade name: KEMPERDUR Deko Coating beige

(Contd. of page 9)

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **Sources**
  - www.echa.europa.eu
  - www.baua.de

  IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:
  - www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp
  - www.dguv.de/ifa/gestis/gestis-dnel-liste

- *** Data compared to the previous version altered.**