

according to 1907/2006/EC, Article 31

Version number 10 (replaces version 9) Revision: 03.08.2022 Printing date 03.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

KEMPEROL BR Waterproofing (M) translucent - Trade name:

HMV8-V0DA-V00A-6TPK - UFI:

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use: intended for professional use only!

Waterproofing - Application of the substance / the mixture

- 1.3 Details of the supplier of the safety data sheet

KEMPER SYSTEM GmbH & Co. KG - Manufacturer/Supplier:

Holländische Strasse 32-36

34246 Vellmar

Deutschland / Germany Telefon: +49 (0)561 / 8295-0 Telefax: +49 (0)561 / 8295-5110 E-Mail: MSDS@KEMPER-SYSTEM.COM

- Further information obtainable from: research & development

- 1.4 Emergency telephone number: Medical Emergency information in case of poisoning:

Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240

(advisory service in German or English language)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation. Eve Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

- Hazard pictograms

The product is classified and labelled according to the CLP regulation.





GHS02

GHS07

- Signal word

- Hazard-determining components of

labelling:

Danger stvrene

maleic anhydride

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-

methylphenyl)amino]-

- Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment. P241

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations

(Contd. on page 2)





according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 10 (replaces version 9) Revision: 03.08.2022

Trade name: KEMPEROL BR Waterproofing (M) translucent

(Contd. of page 1)

- 2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable. - vPvB: Not applicable.

- Determination of endocrine-disrupting properties

53306-54-0 Bis(2-propylheptyl)phthalat

List II

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- **Description:** Mixture: consisting of the following components.

- Dangerous components:		
CAS: 100-42-5	styrene	25-50%
EINECS: 202-851-5	Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
CAS: 53306-54-0	Bis(2-propylheptyl)phthalat	0.5-2.5%
EINECS: 258-469-4	Substance identified as having endocrine disrupting properties (II)	
EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-	≥0.1-<0.5%
	methylphenyl)amino]-	
	Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 13463-67-7	titanium dioxide	≥0.1-<0.5%
EINECS: 236-675-5	Carc. 2, H351	
CAS: 108-31-6		≥0.001-<0.1%
EINECS: 203-571-6	Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	

- Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Do not leave affected persons unattended. Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eye.

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects,

both acute and delayed

- After swallowing:

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- For safety reasons unsuitable extinguishing

agents:

Water with full jet

 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NOx)
Carbon monoxide (CO)

- 5.3 Advice for firefighters

- **Protective equipment:**Do not inhale explosion gases or combustion gases.

(Contd. on page 3)





according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 10 (replaces version 9) Revision: 03.08.2022

Trade name: KEMPEROL BR Waterproofing (M) translucent

(Contd. of page 2)

- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective

equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation Keep away from ignition sources.

- 6.2 Environmental precautions:

- 6.4 Reference to other sections

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers). Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment

and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Store in cool, dry place in tightly closed receptacles.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire - and explosion

protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

Storage

- Requirements to be met by storerooms and

receptacles:

Store only in the original receptacle.

- Information about storage in one common

storage facility:

Store away from foodstuffs.

Further information about storage

conditions:

Protect from frost. Store in dry conditions. Keep container tightly sealed.

Recommended storage temperature: 5-30 °C

- Storage class:

- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

OEL Short-term value: 170 mg/m³, 40 ppm Long-term value: 85 mg/m³, 20 ppm

108-31-6 maleic anhydride

OEL Long-term value: 0.01 ppm

*Inhalable fraction and vapour, Sens

- Regulatory information OEL: 2021 CoP for the Safety, Health and Welfare at Work

- 8.2 Exposure controls

Appropriate engineering controls
 Individual protection measures, such as personal protective equipment

- General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection: When used properly and under normal conditions, breathing protection is not required.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Respiratory protection - Gas filters and combination filters according to (DIN EN 141)

(Contd. on page 4)

(Contd. of page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 10 (replaces version 9) Revision: 03.08.2022

Trade name: KEMPEROL BR Waterproofing (M) translucent

- Hand protection

- Material of gloves

Protective gloves

Check protective gloves prior to each use for their proper condition. Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the

Selection of the glove material on consideration of the penetration times, rates of diffusion and

the degradation After use of gloves apply skin-cleaning agents and skin cosmetics.

Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time (min.): < 480

The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

- Penetration time of glove material The determined penetration times according to EN 16523-1:2015 are not performed under practical

conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is

recommended.

- As protection from splashes gloves made of

the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.1 \text{ mm}$

Penetration time (min.): < 10

- Eye/face protection

Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166

Not determined.

protective clothing (EN 13034) - Body protection:

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- General Information

- Colour: According to product specification Like aromates

- Odour: - Odour threshold: Not determined.

- Melting point/freezing point: Undetermined - Boiling point or initial boiling point and boiling range Undetermined. Not applicable.

- Flammability - Lower and upper explosion limit

- Lower: Not determined. - Upper: Not determined. - Flash point: 31 °C (DIN EN 22719) - Decomposition temperature: Not determined. Not determined.

- pH - Viscosity:

- Kinematic viscosity at 20 °C 95 s (ISO 6 mm) - Dynamic: Not determined.

- Solubility - water: Not miscible or difficult to mix.

- Partition coefficient n-octanol/water (log value)

- Density and/or relative density - Density at 20 °C: 1.16 g/cm3 - Relative density Not determined. Not determined. - Vapour density

- 9.2 Other information

- Appearance:

- Form:

- Important information on protection of health and environment, and on safety.

- Auto-ignition temperature: Product is not selfigniting.

(Contd. on page 5)





according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 10 (replaces version 9) Revision: 03.08.2022

Trade name: KEMPEROL BR Waterproofing (M) translucent

(Contd. of page 4) - Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. - Solvent separation test: - VOC (EC) 3.80 % - Change in condition Not determined. - Evaporation rate - Information with regard to physical hazard classes - Explosives Void - Flammable gases Void - Aerosols Void - Oxidising gases Void - Gases under pressure Void - Flammable liquids Flammable liquid and vapour. - Flammable solids Void - Self-reactive substances and mixtures Void - Pyrophoric liquids Void - Pyrophoric solids Void - Self-heating substances and mixtures Void - Substances and mixtures, which emit flammable gases in contact with Void - Oxidising liquids Void - Oxidising solids Void - Organic peroxides Void - Corrosive to metals Void - Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided:

- 10.3 Possibility of hazardous reactions

Danger of polymerisation.

Reacts with peroxides and other radical forming substances.

No decomposition if used according to specifications.

- 10.4 Conditions to avoid
- 10.5 Incompatible materials:
- 10.6 Hazardous decomposition products:

No further relevant information available.
No dangerous decomposition products known.

(Contd. on page 6)

·ΙΕ



according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 10 (replaces version 9) Revision: 03.08.2022

Trade name: KEMPEROL BR Waterproofing (M) translucent

(Contd. of page 5)

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

	· · · y	·		
- LD/LC50 values relevant for classification:				
100-42-5 styrene				
Oral	LD50	5,000 mg/kg (rat)		
	NOAEL	2,000 mg/kg (rat) (female)		
		1,000 mg/kg (rat) (male)		
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)		
Inhalative	NOAEC	0.21 mg/l (rat) (steam, female. 104 weeks)		
	LOAEC	500 ppm (rat) (steam, male, 6 Hours)		
	LC50/4 h	11.8 mg/l (rat)		
53306-54-	53306-54-0 Bis(2-propylheptyl)phthalat			
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rabbit)		
Reaction	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-			
Oral	LD50	619 mg/kg (rat) (OECD 401)		
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)		
108-31-6 maleic anhydride				
Oral	LD50	400 mg/kg (rat)		
Dermal	LD50	2,620 mg/kg (rabbit)		

- Skin corrosion/irritation

- Serious eye damage/irritation Causes serious eye irritation. May cause an allergic skin reaction.

- Respiratory or skin sensitisation - Germ cell mutagenicity

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

- Carcinogenicity - Reproductive toxicity

Suspected of damaging the unborn child.

Causes skin irritation.

- STOT-single exposure

May cause respiratory irritation. Causes damage to the hearing organs through prolonged or repeated exposure.

- STOT-repeated exposure - Aspiration hazard

Based on available data, the classification criteria are not met.

- Additional toxicological information:

- CMR effects (carcinogenity, mutagenicity

and toxicity for reproduction)

Repr. 2

- 11.2 1110111	- 11.2 information on other nazards				
- Endocrine disrupting properties					
53306-54-0	Bis(2-propylheptyl)phthalat	List II			
80-54-6	2-(4-tert-Butylbenzyl)propionaldehyde	List II			
115-86-6	triphenyl phosphate	List II			

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:		
100-42-5 styrene		
NOEC	1.01 mg/kg (daphnia) (21 days, frehwater)	
LC50	>1-<10 mg/l (Daphnia magna)	
EC50	4.7 mg/l (daphnia) (48 hours, freshwater)	
EC50	4.9 mg/l (ALGAE) (72 hours, freshwater)	
EC50	>1-<10 mg/l (Daphnia magna)	
LC50	10 mg/l (fish) (96 hours, freshwater)	
	4.02 mg/l (Pimephales promelas) (96h)	
53306-54-0 Bis(2-propylheptyl)phthalat		
EC20	>1,000 mg/l (Belebtschlamm) (3h; DIN EN ISO 8192; OECD 209; 88/302/EWG; T.C aer)	
NOEC	93.9 mg/kg (Chironomus riparius) (28d; OECD 218)	
	500 mg/kg (Eisenia fetida/foetida) (56d; OECD 222)	
IC50	>20.5 mg/l (rat)	
	·	(Contd. on page 7)

(Contd. of page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 10 (replaces version 9) Revision: 03.08.2022

Trade name: KEMPEROL BR Waterproofing (M) translucent

LC50/96 h > 10,000 mg/l (Brachydanio rerio (Ricefish)) (OECD 203; ISO7346; 84/449/EWG C.1 stat.) EC50 >100 mg/l (Scenedesmus subspicatus) (72h; 88/302/EWG Part C, S.89 stat.) NOEC >10 mg/l (Brachydanio rerio (Zebrabärbling)) (36d; OECD 210) >1 mg/l (Daphnia magna) (21d; OECD 202; part 2) EC50 >100 mg/l (Daphnia magna) (48h; 79/831/EWG) EC10 265 mg/kg (hu7) (28d; OECD 216) NOEC >1,000 mg/kg (Flowers) (OECD 208) Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-LC50/96 h >100 mg/l (Cyprinus Carpio) (OECD 203 (96 hr)) EC50 >100 mg/l (Scenedesmus subspicatus) (OECD 201; static) EC50 48 mg/l (Daphnia magna) (OECD 202; part 1 static) EC50 >100 mg/l (Cyprinus Carpio) (96h; OECD 203; ISO 7346; 92/69/CEE; C.1 static) NOEC >100 mg/l (Scenedesmus subspicatus) (OECD 201, static)

- 12.2 Persistence and degradability No further relevant information available. - 12.3 Bioaccumulative potential No further relevant information available. - 12.4 Mobility in soil No further relevant information available

- 12.5 Results of PBT and vPvB assessment

- PBT: Not applicable. - vPvR

Not applicable. - 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects

- Additional ecological information:

- General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal according to official regulations

- European waste catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances 15 01 10* packaging containing residues of or contaminated by hazardous substances

17 02 03 plastic

- Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN number or ID number

- ADR, IMDG Void UN1866 - IATA

- 14.2 UN proper shipping name

- ADR. IMDG Void

- IATA **RESIN SOLUTION**

- 14.3 Transport hazard class(es)

- ADR, ADN, IMDG

 Class Void

- IATA



- Class 3 Flammable liquids.

- Label

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 10 (replaces version 9) Revision: 03.08.2022

Trade name: KEMPEROL BR Waterproofing (M) translucent

	(Contd. of page 7)
- 14.4 Packing group	
- ADR, IMDG	Void
- IATA	III
- 14.5 Environmental hazards:	
- Marine pollutant:	No
- 14.6 Special precautions for user	Not applicable.
- 14.7 Maritime transport in bulk according to IMO i	nstruments Not applicable.
- Transport/Additional information:	
- ADR	
- Remarks:	Kein Gut der Kl. 3 gemäß 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code
	ADR / IMDG: Verpackung > 450 l = UN 1866 - Kl. 3 - HARZLÖSUNG, entzündbar - VPIII
	Außerhalb ADR / IMDG = UN 1866 - Kl. 3 - HARZLÖSUNG, entzündbar - VPIII
	Not goods of cl. 3 in accordance with 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code
	ADR / IMDG: Packaging > 450 I = UN 1866 - cl. 3 - RESIN SOLUTION, flammable -
	PGIII Outside ADR / IMDG = UN 1866 - cl. 3 - RESIN SOLUTION, flammable - PGIII
- UN "Model Regulation":	Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

50.000 t

- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed. P5c FLAMMABLE LIQUIDS Seveso category
- Qualifying quantity (tonnes) for the
- application of lower-tier requirements 5,000 t - Qualifying quantity (tonnes) for the
- application of upper-tier requirements
- REGULATION (EC) No 1907/2006 ANNEX
- Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors None of the ingredients is listed.
- 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

(Contd. on page 9)





according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 10 (replaces version 9) Revision: 03.08.2022

Trade name: KEMPEROL BR Waterproofing (M) translucent

(Contd. of page 8)

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- Department issuing SDS:

- Contact:

- Sources

- Date of previous version:

- Version number of previous version:

- Abbreviations and acronyms:

research & development research & development 07.09.2021

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irch: 12: Skin corrosion/irritation – Category 15
Skin Irrit: 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit: 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- www.echa.europa.eu

- www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:

- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp

- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * Data compared to the previous version altered.