

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)


Revision: 22.12.2021


SECTION 1: Identification of the substance/mixture and of the company/undertaking


- 1.1 Product identifier
- Trade name: **KEMPEROL FALLSTOP**
- UFI: JVE9-M044-E00T-5ETJ
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - Identified use: intended for professional use only!
- Application of the substance / the mixture: Coating
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
 - KEMPER SYSTEM LTD
 - Kemper House
 - 30 Kingsland Grange
 - Warrington
 - WA1 4RW
 - www.kempersystem.co.uk
 - enquiries@kempersystem.co.uk
 - phone: +44 (0)1925 445532
 - fax: +44 (0)1925 575096
- Further information obtainable from: research & development
- 1.4 Emergency telephone number:
 - Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen
 - Langenbeckstraße 1; Gebäude 601; 55131 Mainz
 - Tel. Nr.: +49 (0)6131 / 19 24 0
 - Universitätsmedizin der Johannes Gutenberg-Universität Mainz

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
 - Flam. Liq. 3 H226 Flammable liquid and vapour.
 - Acute Tox. 4 H332 Harmful if inhaled.
 - Eye Irrit. 2 H319 Causes serious eye irritation.
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
 - Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
 - The product is classified and labelled according to the CLP regulation.
- Hazard pictograms


GHS02


GHS07


GHS09
- Signal word: Warning
- Hazard-determining components of labelling:
 - reaction mass of ethylbenzene and xylene
 - Urethane bis Oxazolidine
 - Isophorondiisocyanate homopolymer
 - 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
 - Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
 - hexahydromethylphthalic anhydride
 - benzotriazole derivatives
- Hazard statements
 - H226 Flammable liquid and vapour.
 - H332 Harmful if inhaled.
 - H319 Causes serious eye irritation.
 - H317 May cause an allergic skin reaction.
 - H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:
 - EUH204 Contains isocyanates. May produce an allergic reaction.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: **KEMPEROL FALLSTOP**

(Contd. of page 1)

As from 24 August 2023 adequate training is required before industrial or professional use.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:**
- **vPvB:**

Not applicable.
Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- Description:

Mixture: consisting of the following components.

- Dangerous components:

CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	≥12.5-<20%
CAS: 59719-67-4 EINECS: 261-879-6 Reg.nr.: 01-2119983487-19	Urethane bis Oxazolidine Aquatic Chronic 2, H411; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-12.5%
CAS: 53880-05-0 EC number: 931-312-3 Reg.nr.: 01-2119488734-24	Isophorondiisocyanate homopolymer Skin Sens. 1, H317; STOT SE 3, H335	10-12.5%
EC number: 905-588-0 Reg.nr.: 01-2119539452-40	reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	≥2.5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	hydrocarbons, C9, aromatic Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	2.5-10%
CAS: 25550-51-0 EINECS: 247-094-1 Index number: 607-241-00-6 Reg.nr.: 01-2119845474-33	hexahydromethylphthalic anhydride Resp. Sens. 1, H334; Eye Dam. 1, H318; Skin Sens. 1, H317	≥0.1-<0.5%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5 Reg.nr.: 01-2119490408-31	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.25-<0.5%
ELINCS: 400-830-7 Index number: 607-176-00-3 Reg.nr.: 01-0000015075-76	benzotriazole derivatives Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥0.25-<0.5%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.1-<0.25%

- SVHC

25550-51-0 | hexahydromethylphthalic anhydride

- Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information:

Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Do not leave affected persons unattended.
Personal protection for the First Aider.

- After inhalation:

Take affected persons out of danger area and lay down.
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

- After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment in case of complaints.

- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Protect unharmed eye.

- After swallowing:

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

EN_GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: **KEMPEROL FALLSTOP**

(Contd. of page 2)

- 4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media**
- Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.
- For safety reasons unsuitable extinguishing agents:** Water with full jet
- 5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.
Nitrogen oxides (NO_x)
Carbon monoxide (CO)
- 5.3 Advice for firefighters**
- Protective equipment:** Do not inhale explosion gases or combustion gases.
- Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
Avoid contact with skin and eyes
Ensure adequate ventilation
- 6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
Prevent from spreading (e.g. by damming-in or oil barriers).
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling** Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities**
- Storage:**
- Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- Information about storage in one common storage facility:** Store away from foodstuffs.
- Further information about storage conditions:** Recommended storage temperature: 5-30 °C
Store in dry conditions.
Protect from frost.
Keep container tightly sealed.
- Storage class:** 3
- 7.3 Specific end use(s)** No further relevant information available.

EN_GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: **KEMPEROL FALLSTOP**

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

- Regulatory information WEL: EH40/2020

- DNELs

reaction mass of ethylbenzene and xylene

Inhalative	Acute - systemic effects	221 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))
	Long term - systemic effects	221 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))

- Ingredients with biological limit values:

reaction mass of ethylbenzene and xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

BMGV	1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period of exposure Parameter: isocyanate-derived diamine
------	--

- Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Appropriate engineering controls

No further data; see item 7.

- Individual protection measures, such as personal protective equipment

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Respiratory protection:

When used properly and under normal conditions, breathing protection is not required.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2

- Hand protection



Protective gloves

Check protective gloves prior to each use for their proper condition.
Only use chemical-protective gloves with CE-labelling of category III.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves

Recommended materials:
Butyl rubber, BR
Recommended thickness of the material: ≥ 0.5 mm
Penetration time (min.): < 480

- Penetration time of glove material

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.1 mm
Penetration time (min.): < 10

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: **KEMPEROL FALLSTOP**

- Eye/face protection



Tightly sealed goggles

(Contd. of page 4)

- Body protection:

Protective goggles and facial protection - Classification according to EN 166 protective clothing (EN 13034)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Colour:	According to product specification
- Odour:	Characteristic
- Odour threshold:	Not determined.
- Melting point/freezing point:	Undetermined.
- Boiling point or initial boiling point and boiling range	137 °C
- Flammability	Not applicable.
- Lower and upper explosion limit	
- Lower:	Not determined.
- Upper:	Not determined.
- Flash point:	41 °C (DIN EN ISO 1523)
- Auto-ignition temperature:	Product is not selfigniting.
- Decomposition temperature:	Not determined.
- pH	Not determined.
- Viscosity:	
- Kinematic viscosity at 20 °C	107 s (ISO 6 mm)
- Dynamic:	Not determined.
- Solubility	
- water:	Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value)	Not determined.
- Density and/or relative density	
- Density at 20 °C:	1.01 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.

- 9.2 Other information

- Appearance:	
- Form:	Fluid
- Important information on protection of health and environment, and on safety.	
- Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Solvent separation test:	
- VOC (EC)	<26.80 %
- Change in condition	
- Evaporation rate	Not determined.

- Information with regard to physical hazard classes

- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	Flammable liquid and vapour.
- Flammable solids	Void

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: **KEMPEROL FALLSTOP**

(Contd. of page 5)

- Self-reactive substances and mixtures

Void

- Pyrophoric liquids

Void

- Pyrophoric solids

Void

- Self-heating substances and mixtures

Void

- Substances and mixtures, which emit flammable gases in contact with water

Void

- Oxidising liquids

Void

- Oxidising solids

Void

- Organic peroxides

Void

- Corrosive to metals

Void

- Desensitised explosives

Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

- LD/LC50 values relevant for classification:
64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)

59719-67-4 Urethane bis Oxazolidine

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rab)

53880-05-0 Isophorondiisocyanate homopolymer

Oral	LD50	>14,000 mg/kg (rat) (OECD 401)
------	------	--------------------------------

reaction mass of ethylbenzene and xylene

Oral	LD50	5,627 mg/kg (mouse) 3,523 mg/kg (rat)
Dermal	LD50	>4,200 mg/kg (rabbit)
Inhalative	LC50/4 h	29 mg/l (rat)

hydrocarbons, C9, aromatic

Oral	LD50	>3,492 mg/kg (rat) (OECD 401)
------	------	-------------------------------

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: **KEMPEROL FALLSTOP**

(Contd. of page 6)

Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
25550-51-0 hexahydromethylphthalic anhydride		
Oral	LD50	>5,000 mg/kg (rat)
4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate		
Inhalative	LC50/4 h	0.05 mg/l (ATE)
benzotriazole derivatives		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Oral	LD50	3,230 mg/kg (rat) (OECD-guideline 423)
Dermal	LD50	>3,170 mg/kg (rat) (OECD Guideline 402 (Acute Dermal Toxicity))
- Skin corrosion/irritation Based on available data, the classification criteria are not met.		
- Serious eye damage/irritation Causes serious eye irritation.		
- Respiratory or skin sensitisation May cause an allergic skin reaction.		
- Germ cell mutagenicity Based on available data, the classification criteria are not met.		
- Carcinogenicity Based on available data, the classification criteria are not met.		
- Reproductive toxicity Based on available data, the classification criteria are not met.		
- STOT-single exposure Based on available data, the classification criteria are not met.		
- STOT-repeated exposure Based on available data, the classification criteria are not met.		
- Aspiration hazard Based on available data, the classification criteria are not met.		
- 11.2 Information on other hazards		
- Endocrine disrupting properties		
128-37-0	2,6-di-tert-butyl-p-cresol	List II

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

64742-95-6 Solvent naphtha (petroleum), light arom.

LL 50	9.2 mg/l (fish) (96h; OECD 203)
EC50	3.2 mg/l (Daphnia magna) (48h; OECD 202)
EC50	2.6 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)

59719-67-4 Urethane bis Oxazolidine

EC50	87.1 mg/l (Daphnia magna) (48h)
EC50	18.6 mg/l (Selenastrum capricornutum) (72h)

53880-05-0 Isophorondiisocyanate homopolymer

LC50/96 h	>1.51 mg/l (Cyprinus Carpio) (Richtlinie 67/548/EWG, Anhang V, C.1.)
EC50	>3.36 mg/l (Daphnia magna) (OECD 202)
EC50	>10,000 mg/l (Belebtschlamm) (OECD 209)

reaction mass of ethylbenzene and xylene

LC50/96 h	26.7 mg/l (Pimephales promelas)
LC50	1.3 mg/l (ALGAE) (48 h)
	2.6 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h; OECD 203)
EC50	2.2 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
IC50	2.2 mg/l (ALGAE)
NOEC	157 mg/l (Belebtschlamm) (OECD 209)
	1.17 mg/l (Ceriodaphnia dubia) (7d; US EPA 600/4-91/003)
	0.96 mg/l (Daphnia magna) (7 d)
IC50	1 mg/l (Daphnia magna) (24h; OECD 202)

hydrocarbons, C9, aromatic

LL 50	9.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h; OECD 203)
EL50	2.9 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
	3.2 mg/l (Daphnia magna) (48h; OECD 202)
EC50	>99 mg/l (Belebtschlamm) (10 min.; OECD 209)

benzotriazole derivatives

NOEC	100 mg/kg (Eisenia fetida/foetida) (56d; OECD 222)
------	--

(Contd. on page 8)

EN_GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: **KEMPEROL FALLSTOP**

(Contd. of page 7)

LC50/96 h	2.8 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (OECD 203; ISO 7346; 84/449/EWG,C1 stat.)
EC50	>1,000 mg/l (Belebtschlamm) (3h; OECD 209)
EC50	4 mg/l (Daphnia magna) (48h;)
EC10	10 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
EC50	>100 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
NOEC	0.78 mg/l (Daphnia magna) (21d; OECD 202, Part 2)

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

EC50	0.42 mg/l (ALGAE) (OECD 201)
LC50	0.9 mg/l /72 h (fish) (OECD 203 (96 hr))

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal according to official regulations

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances
17 02 03	plastic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT, ENVIRONMENTALLY HAZARDOUS
- **IMDG** PAINT (Solvent naphtha (petroleum), light arom., Urethane bis Oxazolidine), MARINE POLLUTANT
- **IATA** PAINT

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 3 (F1) Flammable liquids.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: **KEMPEROL FALLSTOP**

(Contd. of page 8)

- Label 3

- IMDG



- Class 3 Flammable liquids.

- Label 3

- IATA



- Class 3 Flammable liquids.

- Label 3

- 14.4 Packing group III

- ADR, IMDG, IATA

- 14.5 Environmental hazards: Product contains environmentally hazardous substances: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

- Marine pollutant: Yes
Symbol (fish and tree)

- Special marking (ADR): Symbol (fish and tree)

- 14.6 Special precautions for user Warning: Flammable liquids.

- Hazard identification number (Kemler code): 30

- EMS Number: F-E,S-E

- Stowage Category A

- 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

- Transport/Additional information:

- ADR
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- Transport category 3
- Tunnel restriction code D/E

- IMDG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: KEMPEROL FALLSTOP

(Contd. of page 9)

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- National regulations:

- Other regulations, limitations and prohibitive regulations

- Substances of very high concern (SVHC) according to REACH, Article 57

25550-51-0 | hexahydromethylphthalic anhydride

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction.

- Department issuing SDS:

research & development

- Contact:

research & development

- Date of previous version:

22.12.2021

- Version number of previous version:

7

- Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 1: Acute toxicity – Category 1
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Resp. Sens. 1: Respiratory sensitisation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.12.2021

Version number 8 (replaces version 7)

Revision: 22.12.2021

Trade name: **KEMPEROL FALLSTOP**

(Contd. of page 10)

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- Sources

- www.echa.europa.eu

- www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:

- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp

- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * Data compared to the previous version altered.

EN_GB