KEMCO FL Special Filler

Issued: Vellmar, 2026-05-27

Application area

- As filling compound in combination with KEMCO POX 2K Primer

Features

- Grading curve 0.1 - 0.5 mm
- Kiln-dried

Pack sizes

7.5 kg container

Storage

Cool and dry.

Store in closed original containers in dry rooms at temperatures between +5°C and +25°C.

Consumption

Depending on requirements and field of application.

For further information on application, please refer to the separate technical data sheets and the application instructions.

Disposal

Dispose of in accordance with the official regulations. Further information on disposal can be found in the respective safety data sheets, Section 13.

General information

The times given above are reduced with higher and increased with lower ambient and substrate temperatures. KEMPER SYSTEM products must not be mixed with other manufacturers´ products.

Only for commercial use.

Our technical data sheets / technical information and our technical application advice only reflect the current state of knowledge in our company and our experience with our products. With each new edition, the previous technical information loses its validity. It is therefore essential that you always have the latest data sheet to hand. The latest version can be downloaded from kemperol.de under Media > Downloads. When applying and using our products, a detailed, object-related, qualified check is required in each individual case to determine whether the respective product and/or the application technology meets the specific requirements and purposes. We are only liable for the freedom from defects of our products, but only if our respective product has been used and processed in accordance with our processing guidelines in the technical data sheets. The proper and professional processing of our products is therefore the sole responsibility and liability of the user (processor). Our products are sold exclusively on the basis of our terms and conditions of sale and delivery.