

## KEMCO NQ 0408 Natural Quartz



### Application area

- For new buildings and repair work in combination with KEMPERTEC, KEMPEROL and KEMPERDUR
- To create a bonding bridge with the primers:
  - KEMPERTEC EP Primer,
  - KEMPERTEC EP5 primer
  - KEMCO 1K Primer
 on concrete, screed or sealants (see primer recommendations)
- As a scattering for primers
- To be scattered in KEMPERDUR TC coating
- Indoor and outdoor use

### Features

- Kiln-dried
- Grading curve that is adapted to the intended purpose and compatible with the system

### Pack sizes

25 kg bag

### Storage

Cool and dry.

### Consumption

In order to create a bonding bridge: at least 2 kg/m<sup>2</sup>

For spreading in the primer: at least 2 kg/m<sup>2</sup>

For spreading in the KEMPERDUR® TC: at least 3-5 kg/m<sup>2</sup>

### Properties

|      |                 |
|------|-----------------|
| Form | Granular /solid |
|------|-----------------|

\* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

### CE marking

|                |             |
|----------------|-------------|
| Component to 4 | ETA 03/0025 |
|                | ETA 03/0026 |
|                | ETA 03/0043 |
|                | ETA 03/0044 |

### Application

#### Use as a bonding coat

Substrates like concrete, screed or KEMPEROL water-proofings must be level, dry, firm and free of from any substances which may hinder adhesion. The surfaces must be prepared accordingly and primed with KEMPERTEC EP Primer or KEMPERTEC EP5 primer as well. Scatter approx. 2 kg/m<sup>2</sup> of KEMCO NQ 0408 Natural Quartz into the still wet primer as a bonding coat. As a bonding coat on KEMPEROL Waterproofing systems for the subsequent KEMCO Decor Stone / Natural Stones also KEMCO 1K Primer can be used.

#### As scattering

See technical data sheet KEMPERDUR TC coating resp. the data sheet of the respective primer.

#### PPE

Personal protective equipment must be worn.

We recommend a hand protection and skin protection plan adapted to the workplace. Clean the tools immediately after use with KEMCO MEK Cleaning Agent.

### Disposal

EAK 17 05 04

No hazardous waste, disposal as domestic waste.

### General information

The times given above are reduced with higher and increased with lower ambient and substrate temperatures. KEMPER SYSTEM products must not be mixed with other manufacturers' products.

### Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2023-03-30