

KEMPERDUR AC Park⁺ special filler

Uses

- Quartz sand mixture for creating a coating from KEMPERDUR AC Park⁺

Features

- Graduated grain size
- System compatible and adapted to the specific purpose

Pack size

25 kg paper bag

consumption

At least 4.0 kg/m² (2.5 kg KEMPERDUR AC Park⁺ special filler) KEMPERDUR AC Park⁺ for a layer thickness of 3mm.

Waterproofing packages consist of:

- 15 kg KEMPERDUR AC Park⁺ as Component A
- KEMPEROL CP catalyst powder acc. to Table as a component B
- 25 kg KEMPERDUR AC Park⁺ special filler as Component C.

Shelf Life

Keep cool and dry. The bags must be kept air-tight.

Properties

Form	Granular /solid
------	-----------------

* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

Application

Work steps after preparation of the substrate:

- Mixing in of KEMPEROL CP catalyst powder in KEMPERDUR AC Park⁺
- Mixing in of KEMPERDUR AC Park⁺ special filler

Mixing must be carried out with a slow-running mixing device (preferably a positive mixer) until you achieve a homogeneous mixture.

PPE

For application in enclosed areas ensure there is sufficient ventilation. Always wear personal protective equipment (breathing equipment with filter A/P2, protective gloves, safety goggles).

Important notes

The safety data sheets, identification of the containers, hazard statements and the safety recommendations on the containers must be observed during transportation, storage and application.

Floor finishes are subjected to mechanical stress and should therefore be inspected / maintained on a regular basis. Refinishing may be required depending on the level of wear.

Disposal

Quartz Sand Mixture	solid	EWC 19 12 09
---------------------	-------	--------------

General information

No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2021-03-15