

KEMPEROL 165 fleece



Uses

- For new buildings and repair work
- Reinforcement for KEMPEROL Watgerprofings

Characteristics

- Easier processing due to better non-woven fabric impregnation
- System-tested and matched to the application purpose
- Regulates the layer thickness
- Good adaptability
- Base: Polyester

Pack sizes

Rolls

Length in metres: 50

Width in cm: 105 / 70 / 52.5 / 42 / 35 / 26.25 / 21 / 10.5

Properties

Form	solid
Colour	White
Weight [g/m ²]	approx. 165

* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

Shelf Life

Keep away from dampness, store dry, flat and crease-free.

CE marking

Component to 3	ETA 03/0025
	ETA 03/0026
	ETA 03/0043
	ETA 03/0044

Application

Use

Apply approx. 2/3 of KEMPEROL sealant to the prepared and pre-treated substrate, immediately lay in KEMPEROL 165 Fleece without wrinkles or bubbles and press on. Lay the individual non-woven fabric sheets with an overlap of at least 5 cm. Further fresh-in-fresh with approx. 1/3 KEMPEROL sealant soak the inserted KEMPEROL 165 Fleece completely until saturation, avoid excess material.

Connections to door and window elements etc. with a height of <15 cm (from upper edge of coating) should have at least 5 cm of overlap. Connections and joints to third party products have to be produced with an overlap of at least 10 cm.

Disposal

Fleece	EWG 04 02 21
--------	--------------

General information

No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2023-03-30