

KEMPEROL UP-A cold activator



Uses

- For shortening the processing time for the sealants KEMPEROL V 210 M and KEMPEROL BR M at underground and ambient temperatures between 5 °C and 10 °C.

Pack sizes

0,2 kg in a container

Shelf Life

Can be stored cool, frost-free, dry and unopened. Best before: see container label.

Usage guide

0.2 kg for 20 kg KEMPEROL V 210 M or KEMPEROL BR M sealant.

Properties

Form Liquid

* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

CE marking

Component to 2
ETA 03/0025
ETA 03/0026

Application

KEMPEROL UP-A Cold Activator to be mixed with a stirring stick or slow-running agitator intensively into the resin component until you achieve a homogeneous and streak-free mixture. At V 210 M and BR M directly into the liquid sealant before adding the KEMPEROL CP catalyst powder. Mixing time approx. 1 minute.

If the ambient temperature is 10°C or lower, it is recommended that you store and mix the components at room temperature.

PPE

Personal protective equipment should be worn. We recommend a hand protection and skin protection plan adapted to the workplace. Clean the tools immediately after use with KEMCO MEK Cleaning Agent.

Important notes

KEMPEROL UP-A Cold Activator is subject to specific labelling according to the Ordinance on Hazardous Substances (GefStoffV).

The safety data sheets, the labeling of the containers, the hazard warnings and the safety instructions on the containers must be observed during transport, storage and processing. The BG-Chemie data sheets must be observed during processing.

Do not allow to enter waters, drains or to penetrate the ground.

Disposal

liquid EAK 08 05 01

General information

Times are shortened in the case of higher and are longer in the case of lower ambient temperatures and subsurface temperatures. No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual

case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2023-03-30