

KEMPEROL 500 fleece

Uses

- For new buildings and repair work
- Reinforcement for KEMPEROL 022 waterproofing

Characteristics

- Crack-bridging
- System-tested and matched to the application purpose
- Regulates the layer thickness
- Good adaptability
- Base: Polyester

Pack sizes

Rolls

Length in metres: 50 - Width in cm: 70

Length in metres: 25 - Width in cm: 15

Shelf Life

Keep away from dampness, store dry, flat and crease-free.

Properties

Form	solid
Colour	White

Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

Application

Use

Apply approx. 1 kg KEMPEROL 022 waterproofing to a prepared and pre-treated substrate, immediately roll in the KEMPEROL 500 Fleece without creases and bubbles and press it down. Overlap the individual fleece sections by 5 cm. Subsequently apply approx. 0.8 kg KEMPEROL 022 waterproofing fresh-in-fresh to the KEMPEROL 500 Fleece, ensuring complete saturation, avoid excessive material.

Connections to door and window elements etc. with a height of <15 cm (from upper edge of coating) should have at least 5 cm of overlap. Connections and joints to third party products have to be produced with an overlap of at least 10 cm.

Disposal

Dispose of in accordance with the official regulations. Further information on disposal can be found in the respective safety data sheets, Section 13.

General information

No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and our technical application advice only reflect the current state of knowledge in our company and our experience with our products. With each new edition, the previous technical information loses its validity. It is therefore essential that you always have the latest data sheet to hand. The latest version can be downloaded from kemperol.de under Media > Downloads. When applying and using our products, a detailed, object-related, qualified check is required in each individual case to determine whether the respective product and/or the application technology meets the specific requirements and purposes. We are only liable for the freedom from defects of our products, but only if our respective product has been used and processed in accordance with our processing guidelines in the technical data sheets. The proper and professional processing of our products is therefore the sole responsibility and liability of the user (processor). Our products are sold exclusively on the basis of our terms and conditions of sale and delivery.

Issued: Vellmar, 2024-04-08