

## KEMPERDUR CQ 0408 Colorquarz



ETA 03/0044

### Properties

|        |                    |
|--------|--------------------|
| Colour | anthracite mottled |
|        | grey mottled       |

\* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

### Application

See Technical information sheet KEMPERDUR Deko transparent and KEMPERDUR® TC.

To avoid colour variations or shading over the surface, material from different bags must be mixed in advance.

### Disposal

|       |              |
|-------|--------------|
| solid | EWC 19 12 09 |
|-------|--------------|

### General information

No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2023-03-30

### Uses

- For new buildings and repair work
- For decorative design of wear layers
  - KEMPERDUR TC coating
  - KEMPERDUR AC coating
  - KEMPERDUR quartz covering made of KEMPERDUR Deko transparent and KEMPERDUR CQ 0408 Colorquarz
- As scatterings
- As a coating for concrete, screed, KEMPEROL waterproofing membranes or existing ceramic coatings

### Characteristics

- Lightfast- strong colors
- Resistant to freezing and thawing
- Non-slip

### Pack sizes

25 kg bag

### Shelf Life

Cool and dry.

### CE marking

|                |             |
|----------------|-------------|
| Component to 4 | ETA 03/0025 |
|                | ETA 03/0026 |
|                | ETA 03/0043 |